

**CARVER** S.r.l.  
Via Giovanni XXIII, 36  
20090 Rodano (MI) ITALY  
Tel. (02) 95.00171 (r.a.)  
Fax (02) 95.320.921  
internet: [www.carver.it](http://www.carver.it)



AZIENDA CON SISTEMA DI  
GESTIONE PER LA QUALITÀ  
CERTIFICATO DA DNV  
= UNI EN ISO 9001:2000 =

AZIENDA CON SISTEMA DI GESTIONE  
AMBIENTALE CERTIFICATO DA DNV  
= UNI EN ISO 14001:2004 =

## TECHNICAL DATA SHEET

rev. 00 20/07/2007

## DERGOS VAP (wood soap)

code SO8101

### TECHNICAL DATA *(with room temperature of +23°C and 65% of relative air humidity)*

Appearance	opalescent white liquid
Viscosity	11" F4 ± 1" F4
pH	10.0 ± 1.0
Specific weight	1.00 ± 0.02
Average yield of the product	25-50 m <sup>2</sup> /liter

### DESCRIPTION

Polish on the base of soaps and waxes emulsified in water, especially developed for the maintenance of oiled wooden floors. DERGOS VAP nourishes and cleans the wood, is ready-to-use and suitable for professional as well as for domestic use.

### PACKAGING

0.75-litre plastic bottles with vaporizer.

### DIRECTIONS

Spray DERGOS VAP on the floor and spread it uniformly with a moist cloth. Rinse the cloth every now and then in clear water to remove dirt. After drying, it is advisable to shine with a floor-polisher at low speed, using soft pads.

DO NOT RINSE THE FLOOR WITH WATER.

### NOTICE

- The maintenance with DERGOS VAP can start after 7-10 days in order to allow the complete drying of the impregnation treatment.
- Dilute DERGOS VAP only in water.
- **Attention!** As a general rule, wood floors should not be flooded with plenty of liquid, but wiped with moist cloth.

**Protect from freezing!**

If the original unopened container is stored in a cool and dry place, the product will keep for at least 12 months.

**N.B.** The information contained in this technical data sheet is to the best of our knowledge and experience. Since the conditions of use are beyond our control, no warranty is given or implied.