

Earl's MultiFill

Multi-Purpose Filler
by Timbermate



*Water-Based Filler
For Interior/Exterior Use*

**Wood • Concrete • Drywall
Masonry • Cement Board**

- Indefinite Shelf Life
- Non-Shrinking
- Applies Easily
- Sets Hard



Timbermate[®]group

A subsidiary of Timbermate Products (Pty) Ltd.

U.S. OFFICE:

1042 N. Mountain Suite 291 • Upland, CA 91786

(855) 500-MATE

www.timbermategroup.com

Earl's MulTFill

Multi-Purpose Filler
by Timbermate



P/N	Size	Barcode
MUL07	7 oz.	9315284531999
MUL02	2 lbs.	9315284531869
MUL04	4 lbs.	9315284531876

Preparation - Base material must be sound. Not for use on rotted wood. Make sure area is clean and free of dust. Apply with a wet, plastic putty knife. Ensure the gap is filled. Fill a max. of 1/4" layer at a time. Allow to dry between layers. Can speed drying time by using a heat gun. Drying time is 1-3 hours depending upon the weather and depth of the fill. Sand when dry using 120 grit sandpaper or finer.

■ Ready to Use

If it dries out, add a few drops of water. Keep the container sealed when not in use.

■ Durable

Will not shrink, sink or fall out. Does not contain latex or acrylic.

■ Environmentally Friendly

No acrylic, latex or solvents. VOC free.

■ Indefinite Shelf Life

■ Compatible with Colorants

Always test colorant on the filler prior to use. If using a clear coat, add tint, stain or oxide prior to using. Top coat once dry. MulTFill does not take colorant evenly once dry.

■ Color Matching

Always match color to filler when it is wet. Wet color of filler is the final color when top coated.