

PAREO MAINTENANCE

Protector for oiled wood

Pareo Maintenance is a product designed for the protection and care of outdoor oiled wood. Pareo Maintenance is an emulsion composed of oils, waxes, and UV-resistant additives that help restore the oil degraded by the elements and create additional protection against water.



Drying Time	Careful traffic: 30 minutes Full cure: 12 hours
Available Sizes	946 ml
Applications	Exterior: Ideal for occasional maintenance of decks, siding, docks, fences, structures, garden furniture, doors, windows, playground equipment, flower boxes, and other outdoor wood projects.
Dilution	1:5 : Mix 200 ml of Pareo Maintenance with 1 L of warm water.
Coverage	2500 ft ² /L based on a 1:5 dilution
Surface Types	Oiled wood
Composition	Water, waxes, natural oils, modified oils, UV additives.
COV	0 g/L
Origin	Canada
Tools Cleaning	Water
Disposal of accessories and residues	Wipe off any liquid residue before recycling this container. Consult your municipality for proper disposal of any remaining product.
Storage and Shelf Life	Protect from freezing. Do not use this product if it has frozen. Store in an airtight container at a temperature between 10°C and 25°C. The product has a shelf life of 12 months under these conditions.
Guarantee	Guarantee: Prato-Verde guarantees the quality of its products. They conform to the description provided in the technical data sheets and on the labels suitable for the intended use, in accordance with the instructions written by the company. However, since the manufacturer has no control over the circumstances, methods, and conditions of use, this guarantee only covers the high quality of Prato-Verde products.

Technical Specifications Preparation

1. Wait at least 10 days before beginning maintenance on a freshly oiled terrace.
2. Vacuum or sweep to eliminate any dust or residues.
3. Shake well before each use.
4. Add 200 ml of PAREO MAINTENANCE per liter of warm water and mix thoroughly.
5. Transfer into a bottle equipped with a spray nozzle.

Technical Specifications Application

1. Spray a fine layer of the pre-prepared mixture onto a section of the wood to be treated.
2. Spread it evenly along the wood grain using a mop, sponge, or cloth.
3. Allow the wood to dry without rinsing.
4. Avoid applying too much product in order to prevent a sticky or uneven result.

Tips

Mix well until homogeneous before each use. Apply sparingly to avoid a sticky and uneven surface.

WARNINGS

Keep out of reach of children.