

HEMP OIL

*First pressed Hemp Oil
Zero solvents, Zero VOC*

Hemp Oil is a natural, pure and first pressed oil designed for finishing all interior wooden projects, including food surfaces. Hemp Oil protects against water and offers a matte finish.



Number of Coats	3 to 6 coats
Drying Time	Between coats: 24 to 48 hours Use: 2 days First wet cleaning: 21 days
Available Sizes	946 ml
Sheen	Matte
Applications	Interior: Ideal for food surfaces such as countertops, tables, butcher blocks, as well as furniture, accessories, and other indoor wood projects.
Dilution	For faster drying, mix 1 L of Hemp Oil with 300 ml of Citrus Solvent.
Durability	Food contact surfaces: 3 to 12 months Structures, walls, ceilings, and woodwork: 1 to 3 years Furniture: 1 to 5 years Floors: 1 year
Surface Types	Wood, cork
Advantages	Preserves the natural look of wood Abrasion resistant Protects against water, alcohol, and stains Washable and durable
Coverage	120 to 230 ft ² /L
Compatibility	Can be covered with: Secondo, Secondo Mono, Secondo Cera, Secondo Fast, Tavolo. Always perform a preliminary test to ensure product suitability and compatibility. Can be applied over: Oils, stains, waxes, and chalk paints. Can be covered with: Oils, varnishes, waxes, hybrid finishes, lacquers, and paints.
Composition	First pressed Hemp oil
COV	0 g/L
Viscosity	28 sec. +/- 2 sec. with #4 Ford Cup (Clear)
Origin	Canada
Tools Cleaning	Prato-Verde Tools Cleaner and Thinner
Disposal of accessories and residues	After use, soak the rags in water or lay them flat to dry before disposal. Wipe off any liquid residue before recycling the container. Any leftover product should be brought to your municipality's eco-center.
Maintenance	For regular cleaning: SECONDO CLEAN To revive shine and enhance protection every 2 to 3 months: SECONDO MAINTENANCE For intensive cleaning (degreasing, deep cleaning), as needed only: SECONDO PREP
Storage and Shelf Life	Keep the product in a sealed container at a temperature between 10°C and 25°C for storage. Under these conditions, the product will maintain its quality for at least 5 years. If the product has been exposed to cold temperatures, allow it to return to room temperature for 24 hours before using.
Guarantee	Guarantee: Prato-Verde guarantees the quality of its products. They conform to the description provided in the technical data sheets and on the labels suitable for the intended use, in accordance with the instructions written by the company. However, since the manufacturer has no control over the circumstances, methods, and conditions of use, this guarantee only covers the high quality of Prato-Verde products.

Technical Specifications Preparation

1. Apply at a temperature above 15 °C.
2. Ensure the wood is free from any previous finish and meticulously sanded with 100 or 120 grit sandpaper.
3. Dust off using a vacuum cleaner.
4. It is recommended to clean the wood with PRATO PREP to remove dust particles, reduce tannins, and enhance colour intensity.

Technical Specifications Application

1. Thoroughly mix with a stirring stick.
2. Apply a generous coat of oil until the wood is saturated using a staining pad, a cotton cloth, or a staining applicator.
3. After 30 to 60 minutes, remove any excess oil by rubbing the surface with a cotton cloth.
4. Allow 24 to 48 hours for drying.
5. Repeat all previous steps for subsequent coats.

Further Treatment

The greatest advantage of oil in wood treatment lies in its ease of maintenance and repair. The key to well-maintained oiled wood is prevention. The longer the interval between treatments, the longer the process will take. When SECONDO CLEAN and SECONDO MAINTENANCE products are no longer sufficient to keep your oiled wood in good condition, it's a sign that it's time to consider applying a new layer of oil.

Good general condition (Reduced liquid resistance):

1. Clean the wood with SECONDO CLEAN.
2. Apply a coat of HEMP OIL according to the product instructions.
3. No sanding or stripping required.

Good general condition (Stains or small damaged areas):

1. Sand the damaged area with 120-grit sandpaper.
2. Apply three to six coats of HEMP OIL to the sanded area following the product instructions.

Medium general condition (Slight discolouration, multiple stains, reduced liquid resistance):

1. Clean the wood with SECONDO PREP.
2. Apply several coats of HEMP OIL according to the product instructions.
3. No sanding or stripping required.

Poor general condition (Severe discolouration, graying surface, no liquid resistance, many stains or damaged areas):

1. If cleaning with SECONDO PREP does not remove the stains and graying, repeat the initial procedure for HEMP OIL.

Tips

For a smoother and more even finish, lightly sand between coats with 600 or 800 grit sandpaper.

WARNINGS

Keep out of reach of children.