

BRIO

Finishing oil for wooden walls and ceilings Monocoat

Brio is an oil designed for wooden walls, ceilings, structures and frames. In one single application, Brio colours, seals and waterproofs wood without hiding its natural details.



INTERIOR

Number of Coats	1 to 2 coats. For a deeper colour, apply a second coat after 24 hours.
Drying Time	Handle with care: 18 to 24 hours Between coats: 18 to 24 hours Full cure: 7 days
Available Colors	00 Colourless, 01 Cherry, 03 Medium Oak, 04 Charcoal, 06 Red Fox, 08 American Walnut, 11 Choco Wood, 13 Maple Brown, 15 Dark Oak, 17 Old Pine, 19 White, 20 Cappuccino, 21 Grey, 22 Natural, 23 Teak, 25 Burnt Wood, 26 Sand, 36 Smokey, 41 Ash Grey, 43 Driftwood, 44 Pale Walnut and 45 Pebble
Available Sizes	20 ml (Sample), 237 ml, 946 ml, 3,78 L and 18,9 L
Sheen	Matte
Applications	Interior: Ideal for walls, ceilings, woodwork, beams, doors, paneling, moldings, structures, accessories, and decorative furniture.
Surface Types	Wood, cork
Advantages	Preserves the natural look of wood Protects against moisture Prevents wood discolouration Washable and durable
Durability	8 to 15 years.
Coverage	Softwoods : 150 to 225 ft ² /L Hardwoods : 225 to 300 ft ² /L
Compatibility	Can be covered with: Brio Zero, Secondo, Secondo Mono, Secondo Cera, Secondo Fast. Always perform a preliminary test to ensure product suitability and compatibility. Can be applied over: Oils, stains, waxes, and chalk paints. Can be covered with: Oils, varnishes, waxes, hybrid finishes, lacquers, and paints.
Composition	Blend of vegetable oils, iron oxides, isoparaffin, lead-free and cobalt-free drier.
COV	430 g/L
Viscosity	20 sec. +/- 2 sec. with #4 Ford Cup (Clear)
Origin	Canada
Tools Cleaning	Prato-Verde Tools Cleaner and Thinner
Disposal of accessories and residues	After use, soak the rags in water or lay them flat to dry before disposal. Wipe off any liquid residue before recycling the container. Any leftover product should be brought to your municipality's eco-center.
Maintenance	For regular cleaning: SECONDO CLEAN To revive shine and enhance protection every 2 to 3 months: SECONDO MAINTENANCE For intensive cleaning (degreasing, deep cleaning), as needed only: SECONDO PREP
Storage and Shelf Life	Keep the product in a sealed container at a temperature between 10°C and 25°C for storage. Under these conditions, the product will maintain its quality for at least 5 years. If the product has been exposed to cold temperatures, allow it to return to room temperature for 24 hours before using.
Guarantee	Guarantee: Prato-Verde guarantees the quality of its products. They conform to the description provided in the technical data sheets and on the labels suitable for the intended use, in accordance with the instructions written by the company. However, since the manufacturer has no control over the circumstances, methods, and conditions of use, this guarantee only covers the high quality of Prato-Verde products.

Technical Specifications Preparation

1. Apply at a temperature above 15 °C.
2. The wood must be free from any previous finish and meticulously sanded with 100 or 120 grit sandpaper.
3. Dust off using a vacuum cleaner.
4. After sanding, it is recommended to clean the wood with PRATO PREP to remove dust particles, reduce tannins, and enhance colour intensity.
5. Perform a test of the product on a hidden surface and let it dry for 24 hours to confirm the result, as it may vary depending on the type of wood used.

Technical Specifications Application

Manual Application:

1. Thoroughly mix with a stick before and during application.
2. Apply in a thin coat using circular motions until the wood is saturated using a STAIN APPLICATOR, POLYCOTTON RAGS, stain applicator, short-haired roller, or brush.
3. After 5 to 15 minutes, wipe the surface dry with clean POLYCOTTON RAGS to remove any excess oil.
4. Clean tools and accessories used with TOOLS CLEANER AND THINNER, and soak oil-saturated cloths in water before disposing of them in the trash.
5. Allow 18 to 24 hours to dry.
6. Optional: Repeat all previous steps for applying a second coat.

Mechanical Application:

1. Thoroughly mix with a stick before and during application.
2. Apply the oil using a trowel or short-haired roller.
3. After 5 to 15 minutes, polish using a floor polisher with a white or beige pad.
4. If there is excess oil after polishing, place a POLYCOTTON RAG under the pad and run the polisher again to remove excess oil. Replace the cloth when saturated with oil.
5. Alternatively, apply the oil directly with the polisher by adding a small amount of oil to the center of the pad and rubbing until the product is evenly applied.
6. Clean tools and accessories used with TOOLS CLEANER AND THINNER, and soak oil-saturated cloths in water before disposing of them in the trash.
7. Allow 18 to 24 hours to dry.
8. Optional: Repeat all previous steps for applying a second coat.

Further Treatment

The greatest advantage of oil in wood treatment is its ease of maintenance and repair. The key to well-maintained oiled wood is prevention. The longer the interval between treatments, the longer the treatment will take. Once SECONDO CLEAN and SECONDO MAINTENANCE are no longer sufficient to keep your oiled wood in good condition, it's a sign that it's time to consider applying a new coat of oil.

BRIO requires no further treatment for a long time, unless there are stains or damage to small localized areas.

For areas in generally good condition (with stains or small localized damage):

1. Sand the damaged localized area with 120-grit sandpaper.
2. Reapply BRIO finishing oil to the sanded area following the product's instructions.

As needed, within 8 to 15 years:

1. Clean the wood with SECONDO PREP.
2. Apply a coat of BRIO following the product's instructions.
3. No sanding or stripping required.

Tips

Colours can be mixed to create unique shades. For a slightly deeper colour, apply a second coat after 24 hours. For a lighter colour, mix with Brio Colourless. The colour 00 - Colourless provides an amber finish and highlights the wood grain. The colour 22 - Natural has a slightly whitened appearance. It helps maintain the whiteness of white woods (pine, maple, cherry, spruce, beech, aspen, etc.). It is strongly recommended to perform a test beforehand on open-grain and coloured woods (oak, walnut, mahogany, elm, etc.).

WARNINGS

Keep out of reach of children. Keep away from flames or sparks.

DANGER OF COMBUSTION: Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.