

SECONDO MAINTENANCE

Protector for oiled wood

Secondo Maintenance is an emulsion of oils and waxes designed for the protection and care of interior oiled wood. Secondo Maintenance repairs, protects against water and lightly enhances the sheen of oiled wood.



Drying Time	Careful traffic: 30 minutes Full cure: 12 hours
Available Sizes	946 ml
Coverage	2500 ft ² /L based on a 1:5 dilution
Applications	Interior: Ideal for occasional maintenance of floors, stairs, furniture, kitchen cabinets, vanities, countertops, tables, and any other oiled wood surfaces.
Dilution	1:5 : Mix 200 ml of Secondo Maintenance with 1 L of warm water.
Surface Types	Oiled wood
Composition	Water, waxes, natural oils, modified oils, UV inhibitors.
COV	0 g/L
Origin	Canada
Tools Cleaning	Water
Disposal of accessories and residues	Wipe off any liquid residue before recycling this container. Consult your municipality for proper disposal of any remaining product.
Storage and Shelf Life	Protect from freezing. Do not use this product if it has frozen. Keep the product in a sealed container at a temperature between 10°C and 25°C for storage. Under these conditions, the product will maintain its quality for at least 5 years.
Guarantee	Guarantee: Prato-Verde guarantees the quality of its products. They conform to the description provided in the technical data sheets and on the labels suitable for the intended use, in accordance with the instructions written by the company. However, since the manufacturer has no control over the circumstances, methods, and conditions of use, this guarantee only covers the high quality of Prato-Verde products.

Technical Specifications Preparation

1. Wait at least 10 days before beginning maintenance on a freshly oiled floor.
2. Vacuum or sweep to eliminate any dust or residues.
3. Shake well before each use.
4. Add 200 ml of SECONDO MAINTENANCE per liter of warm water and mix.
5. Pour into a bottle equipped with a spray nozzle.

Technical Specifications Application

1. Spray a fine coat of the pre-prepared mixture onto a section of the wood to be treated.
2. Spread evenly along the wood grain using a mop, sponge, or cloth.
3. Allow the wood to dry without rinsing.
4. Avoid applying too much to prevent a sticky or uneven result.

Tips

Mix well until homogeneous before each use. Apply sparingly to avoid a sticky and uneven surface.

WARNINGS

Keep out of reach of children.