

BRIO ZERO

Hybrid finish for wooden walls and ceilings.
Monocoat, Zero solvents

Brio Zero is an emulsion of water and oils designed for wooden walls, ceilings, structures and frames. In one single application, Brio Zero colours, seals and waterproofs wood without hiding its natural details.



Number of Coats	1 to 2 coats. For a deeper colour, apply a second coat after 6 to 18 hours.
Drying Time	Handle with care: 6 hours Between coats: 6 to 18 hours Full cure: 2 days
Available Colors	100 Colourless, 101 Natural, 102 White, 103 Grey, 104 Cherry, 105 Medium Oak, 106 Old Pine, 107 Burnt Wood, 108 Choco Wood, 109 Dark Oak, 110 Maple Brown, 111 Sand, 112 Smokey, 113 Pale Walnut, 114 American Walnut, 115 Ash Grey, 116 Driftwood and 117 Pebble
Available Sizes	20 ml (Sample), 237 ml, 946 ml, 3,78 L and 18,9 L
Sheen	One coat : Matte 2 to 4 % Two coats : Matte 5 to 7 %
Applications	Interior: Ideal for walls, ceilings, woodwork, beams, doors, paneling, moldings, structures, accessories, and decorative furniture.
Surface Types	Wood, cork
Advantages	Fast application and drying Protects against moisture Prevents wood discolouration Washable and durable
Durability	8 to 15 years.
Coverage	100 to 200 ft ² /L
Compatibility	Always perform a preliminary test to ensure product suitability and compatibility. Can be applied over: Oils and stains. Can be covered with: Oils, varnishes, and waxes.
Composition	Blend of modified vegetable oils, water, UV filters, iron oxides.
COV	< 8 g/L
Viscosity	16 sec. +/- 2 sec. with #4 Ford Cup (Clear)
Origin	Canada
Tools Cleaning	Soapy water
Disposal of accessories and residues	Wipe off any liquid residue before recycling this container. Consult your municipality for proper disposal of any remaining product.
Maintenance	For regular cleaning: SECONDO CLEAN To revive shine and enhance protection every 2 to 3 months: SECONDO MAINTENANCE For intensive cleaning (degreasing, deep cleaning), as needed: SECONDO PREP
Storage and Shelf Life	Protect from freezing. Do not use this product if it has frozen. Keep the product in a sealed container at a temperature between 10°C and 25°C for storage. Under these conditions, the product will maintain its quality for at least 5 years.
Guarantee	Guarantee: Prato-Verde guarantees the quality of its products. They conform to the description provided in the technical data sheets and on the labels suitable for the intended use, in accordance with the instructions written by the company. However, since the manufacturer has no control over the circumstances, methods, and conditions of use, this guarantee only covers the high quality of Prato-Verde products.

Technical Specifications Preparation

1. Apply at a temperature above 10 °C.
2. The wood must be free from any previous finish and meticulously sanded with 150 grit sandpaper.
3. Dust off using a vacuum cleaner.
4. After sanding, it is recommended to clean the wood with PRATO PREP to remove dust particles, reduce tannins, and enhance colour intensity.
5. Perform a test of the product on a hidden surface and let it dry for 24 hours to validate the result, as it may vary depending on the type of wood used.

Technical Specifications Application

1. Thoroughly mix with a stick before and during application.
2. Apply generously until the wood is saturated using a STAIN APPLICATOR, roller, or staining brush.
3. After 5 minutes, if needed, even out the surface with a brush to remove any excess product.
4. Clean tools and accessories used with soapy water.
5. Allow 6 to 18 hours to dry.
6. Optional: For the application of a second coat, if more than 24 hours have passed since the first application, sand using 150 grit sandpaper before repeating all previous steps.

Further Treatment

The greatest advantage of oil in wood treatment is its ease of maintenance and repair. The key to well-maintained oiled wood is prevention. The longer the interval between treatments, the longer the process will take. Once SECONDO CLEAN and SECONDO MAINTENANCE are no longer sufficient to keep your oiled wood in good condition, it's a sign that it's time to consider applying a new coat of oil.

BRIO ZERO requires no further treatment for a long time, unless there are stains or damage to small localized areas.

For areas in generally good condition (with stains or small localized damage):

1. Sand the damaged localized area with 120-grit sandpaper.
2. Reapply BRIO ZERO finishing oil to the sanded area following the product's instructions.

As needed, within 8 to 15 years:

1. Clean the wood with SECONDO PREP.
2. Apply a coat of BRIO ZERO following the product's instructions.
3. No sanding or stripping required.

Tips

Colours can be mixed to create unique shades. For a slightly deeper colour, apply a second coat after 6 to 18 hours. For a lighter colour, mix with Brio Zero Colourless. The colour 100 - Colourless provides a wet finish and highlights the wood grain. The colour 101 - Natural has a slightly whitened appearance. It helps maintain the whiteness of white woods (pine, maple, cherry, spruce, beech, aspen, etc.). It is strongly recommended to perform a test beforehand on open-grain and coloured woods (oak, walnut, mahogany, elm, etc.).

WARNINGS

Keep out of reach of children.