

Technical Data Sheet

Brio

Wooden walls & ceilings oil

Brio is an oil designed to be applied on walls, ceilings, structures and other wooden surfaces. In one single application, Brio colors, seals and waterproofs without hiding details.

Preparation

Shake well before and while using. Apply at a temperature above 15 °C. Wood must be sanded with 120 grit sandpaper. Vacuum to dust off.

Prior to application on maple wood, wet the wood, let dry 2 hours and sand lightly with a 220 grit sandpaper.

Application

Apply with a stain applicator, a cloth or a stain pad. **After 5 to 15 minutes, completely wipe off the surface with a cloth to remove any excess oil.**

Number of Coats

1 coat

For interior windows, it is required to apply 2 coats of Secondo over Brio.

For a more intense color, it is possible to apply a second coat after 24 hours.

Drying Time

24 hours

Covering

170 to 300 sq ft / L

Tools Cleaning

Oil thinner

Composition

Safflower oil, tung oil, linseed oil, isoparaffin, iron oxide, vegetal wax, siccativ.

Maintenance

- Yearly cleaning : Bonito soap
- To refresh and make the surface shine : Luminoso



- Colors and seals wood in a single application
- Waterproofs wooden surfaces
- Available in 16 colors
- Prevents wood discoloration
- Great coverage
- Leaves no film on the wood surface
- Lets the wood vein show through
- Easy to apply
- Easy care
- Lets the wood breathe
- Low odor

Project Types

Paneling for walls and ceilings, moldings, structures, interior doors

Surface Types

Wood, Cork

Compatibility

- Can be applied on : Wood oils, wood stains.
- Can be covered with : Secondo, wood varnish, wood wax.

VOCs

419 g / L

Durability

8 to 15 years

Storage

Keep in an airtight container

Residues Disposal

Consult your municipality to properly dispose the remains of this product.

Origin

Italy

DANGER OF COMBUSTION - Keep out of reach of children.
Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

Warranty

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Prato-Verde products.

Sheen

Satin matt (2 à 4%)

Sizes

- 20 ml (sample)
- 237 ml
- 946 ml
- 3.78 L
- 18.9 L

Colors

- 00 - Natural
- 01 - Cherry
- 02 - Rosewood
- 03 - Medium Oak
- 04 - Charcoal
- 06 - Red Fox
- 08 - American Walnut
- 09 - Cinnamon
- 10 - Africajou
- 11- Choco Wood
- 13 - Maple Brown
- 15 - Dark Oak
- 17 - Old Pine
- 19 - White
- 20 - Cappuccino
- 21 - Grey