

## Technical Data Sheet

### Pareo

#### Exterior Finishing Oil

Pareo is a non-film forming oil for exterior wood coloration and finishing. Pareo waterproofs the wood and prevents discoloration due to UV rays.

#### Preparation

Moisture level of wood needs to be 15% or less before beginning (Wait 3 months before applying on new wood, one year on new treated wood.). Stir well with a stick before and while using. Do not apply in sunlight or at a temperature below 10 °C. The wood must be completely dry, clean and sanded with a 80 grit paper.

For an application on sawn wood or to obtain a softer coloration, it's possible to dilute Pareo with an equal part or less of Pareo Colourless Base.

Do not apply only the Pareo Colourless Base on surfaces exposed to sun. The dilution of Pareo with Pareo Colourless Base decreases UV resistance. The pigments contained in the tinted Pareo are essential for the wood conservation.

#### Application

Apply with a stain brush or a stain pad in very thin coats, wipe off any excess oil with a cotton rag.

If more than 24 hours have passed since the first application, sand lightly with a 120 grit paper before the second application.

The use of a spray gun is highly unsuitable for vertical application. For horizontal surfaces, wipe off any excess oil after spray gun application.

#### Drying Time

- Water resistance : 6 hours
- Between coats: 12 to 18 hours
- Cautious traffic : 18 to 24 hours
- Complete drying : 7 days

#### Number of coats

2 coats



- Prevents discoloration due to UV rays
- Waterproofs wood surfaces
- Lets the wood vein transpire
- Does not make a film on the wood surface
- Protects against mildew
- Protects against destructive insects
- Does not blister or whiten with time
- Can be reapplied without stripping

#### Project Types

Walls covering, terrace, windows and doors, roof shingles, outdoor Furniture, fences, woodworks, flower boxes, children playgrounds

#### Surface Types

Untreated wood, commercial treated dry wood (1 year), restored wood (stained or oiled)

#### Maintenance

Clean with water and scrub. When the finish becomes dull and slightly discolored (after 1 to 6 years), apply one coat of colorless Pareo to revive the color and waterproof the wood.

### Coverage

Sanded wood : 80 to 275 sq ft / L

Sawn wood (untreated) : 40 to 100 sq ft / L

### Durability

Vertical surfaces : 2 to 6 years

Horizontal surfaces : 1 to 3 years

### Compatibility

**Compatible** with most clear or semi-clear exterior oil based Stains, Uno colored oil, exterior impregnation products. **Incompatible** with exterior water based and hybrid Stains, exterior varnishes, film forming products.

It's strongly recommended reading carefully the technical sheet of the product and making prior test to ensure the propriety and compatibility of the products.

### Dilution

Pareo Colourless Base

### Tool Cleaner

Finishing oil thinner

### Composition

Vegetal oil, iron oxide, isoparaffin, unleaded siccative

### Storage

Keep in airtight container.

### Residues Disposal

Consult your municipality for proper disposal procedure of this product residues.

**DANGER OF COMBUSTION** - Keep out of reach of children.  
Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

### Warranty

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Prato-Verde products.

### Sheen

2 to 4 %

### VOCs

437 g / L

### Sizes

- 20 ml (sample)
- 946 ml
- 3.78 L
- 18.9 L

### Colors

- 01 - Cherry
- 02 - Rosewood
- 03 - Medium Oak
- 04 - Charcoal
- 06 - Red Fox
- 08 - American Walnut
- 09 - Cinnamon
- 10 - Africajou
- 11 -Choco Wood
- 13- Maple Brown
- 15 - Dark Oak
- 17 - Old Pine
- 19 - White
- 20 - Cappuccino
- 21- Grey

### Origin

Italy