

## Technical Data Sheet

### Secondo

#### Wooden Floor Oil

Secondo is an oil designed to be applied on floors or other wooden surfaces. Secondo oil waterproofs and resists to abrasion, it can be used alone or with Uno colored oil.

#### Preparation

Shake well before and while using. Apply at a temperature above 15 °C. Wood must be sanded with 100 or 120 grit paper. Vacuum to dust off.

**Prior to application on maple wood**, wet the wood, let dry 2 hours and lightly sand with a 220 grit sandpaper.

#### Application

Apply with a stain applicator, a cloth or a stain pad. **After 5 to 15 minutes, completely wipe off the surface with a cloth to remove any excess oil.**

For an application on furniture and woodwork, it is recommended to pumice off with a 000000 steel wool or sand with 800 grit sandpaper between each coat.

If more than 72 hours have passed since applying the last coat, lightly sand the surface with a 120 grit sandpaper before applying the next coat.

#### Number of Coats

On Uno treated wood : 2 coats

On untreated wood : 3 coats

On heavy traffic surfaces such as kitchen countertops and work area, it is recommended to apply an additional coat.

#### Drying Time

- Between coats : 24 hours
- Careful use : 24 hours
- Put back rugs and furniture : 7 days
- First damp cleaning : 10 days

#### Covering

190 to 360 sq ft / L



- Good abrasion resistance
- Waterproofs wood surfaces
- Great coverage
- Leaves no film on the wood surface
- Lets the wood vein show through
- Easy to apply
- Easy care
- Lets the wood breath
- Low odor

#### Project Types

Floors, furniture, kitchen cabinets, countertops, islets, interior windows and doors, woodwork, walls and ceilings.

#### Surface Types

Wood, cork

#### Compatibility

- Can be applied on : Wood oil, wood stain
- Can be covered with : Wood oil, wood varnish, wood wax

#### Durability

Heavy traffic : 2 to 3 years  
Low traffic : 5 to 7 years

**Maintenance**

Bonito soap, Sancio protector, Luminoso polish

**Tools Cleaning**

Oil thinner

**Storage**

Keep in an airtight container.

**Composition**

Safflower oil, tung oil, linseed oil, vegetal wax, isoparaffin, siccativo.

**Residues Disposal**

Consult your municipality to properly dispose the remains of this product.

**DANGER OF COMBUSTION** - Keep out of reach of children.  
Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

**Warranty**

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Prato-Verde products.

**Sheen**

Satin matt (5 à 7 %)

**VOCs**

409 g / L

**Sizes**

- 20 ml (sample)
- 237 ml
- 946 ml
- 3.78 L
- 18.9 L

**Color**

Colorless

**Origin**

Italy