

Tavolo

Oil for Wooden Countertops & Tables

Tavolo was developed to be applied on wooden countertops, kitchen islands or tables. Tavolo Oil waterproofs wood and is abrasion resistant.

The *Colorless* version provides a honeyed tone and can be used on all types of wood.

The *Natural* version is used to preserve the whiteness of white woods (white pine, maple, cedar, spruce, beech, aspen) or white and gray colored wood (e.g. *White* or *Gray Uno* coloring oil). Do not use the *Natural* version on open grain woods (oak, walnut, mahogany, elm) or colored woods (except for white or gray).

Preparation

Shake well before and while using. Apply at a temperature above 15 °C. Wood must be sanded with 100 or 120 grit sandpaper. Vacuum to dust off. **Prior to application on maple wood**, wet the wood, let dry 2 hours and lightly sand with a 220 grit sandpaper.

Application

Apply with a stain applicator, a cloth or paintbrush. **After 5 to 15 minutes, wipe off the surface with a cloth to remove any excess oil.** For more information, read the technical data sheet available online at prato-verde.com.

If more than one coat is applied, it is recommended to sand with a 800 grit sandpaper between coats.

Number of Coats

1 to 2 coats

Applying additional coats can increase the gloss of the finish. Do not exceed 3 coats.

Drying Time

- Between coats : 24 hours
- Careful use : 24 hours
- First damp cleaning : 10 days

Covering

150 to 290 sq ft / L



- Good abrasion resistance
- Waterproofs wood surfaces
- Provides great resistance against liquids, such as tea, wine, juice
- Microporous finish, won't crack or peel off
- Allows the wood vein to show through
- Easy to apply
- Easy care
- Low odor
- Great coverage

Project Types

Countertops, kitchen islands, kitchen and living room tables

Surface Types

Wood, cork

Compatibility

- Can be applied on : Wood oil, wood stain
- Can be covered with : Wood oil, wood varnish, wood wax

Durability

1 year

Sheen

Satin matt (5 à 7 %)

Maintenance

Bonito soap, Sancio protector

Dilution

In very hot and humid weather, it is recommended to dilute with 5 to 15 % oil thinner.

Tools Cleaning

Oil thinner

Storage

Keep in an airtight container.

Composition

Safflower oil, tung oil, linseed oil, vegetal wax, isoparaffin, siccative.

Residues Disposal

Consult your municipality to properly dispose the remains of this product.

DANGER OF COMBUSTION - Keep out of reach of children.
Materials such as rags used with this product may begin to burn by themselves. After use, put rags in water or lay flat to dry, then discard.

Warranty

Tembi products guarantee the quality of its products. They comply with the description given in the data sheets and proper labels for their intended use, in accordance with the instructions indicated by the company. However, since the manufacturer has no control over the circumstances, methods and usage conditions, this warranty covers only the high quality of Prato-Verde products.

VOCs

299 g / L

Sizes

- 20 ml (sample)
- 500 ml

Colors

Colorless, natural

Origin

Italy